



GT-750F(L)

Fast Acquisition high-Sensitivity 48 Channels Bluetooth-GPS Receiver With Data Logger functionality

The GT-750F(L) is a single board of Bluetooth-GPS receiver for customers who require easy system integration and minimal development risk.

FEATURES

- **Acquire and track 48 satellites simultaneously**
- SiRF-IV simultaneous time-frequency search bins
- **Signal detection better than -163dBm**
- Reacquisition sensitivity -155Bm
- **Cold start < 30 seconds at -147dBm**
- Hot start < 1sec under open sky
- 2.5m CEP accuracy
- **SBAS (WAAS, EGNOS) support**
- **2M Bytes flash memory for data logging, stores up to 250,000 data records**
- Log data can be exported to mapping software such as Google Earth and TrackMaker
- Logging data interval programmable: by time or distance
- Bluetooth version 2.0 compliant
- Compatible with Bluetooth devices with Serial Port Profile (SPP)
- Support G-mouse function via USB cable
- Charger circuitry and battery socket for N3650 Li-ION battery
- More than 20 hours of operation
- Dimension:73x44x21 mm

The GT-750F(L) is optimized for good performance and low cost. Its 48 parallel channels and SiRF_IV search bins provide short start-up time and fast signal acquisition. Having fast time-to-first-fix and high sensitivity, the GT-750F(L) offers good navigation performance even in urban canyons.

The GT-750F(L) is capable of keeping up to 256,000 records or positions, including longitude, latitude, speed, UTC, and tag data. The location histories can be exported to mapping software such as Google Earth or TrackMaker.

Satellite-based augmentation systems, such as WAAS and EGNOS, are supported to yield improved accuracy.

The onboard patch antenna provides good signal reception. It provides fast satellite signal acquisition and short startup time. Acquisition sensitivity of -155dBm and tracking sensitivity of -160dBm offers good navigation performance even in urban canyons having limited sky view.

Class 2 Bluetooth offers up to 10 meters of wireless operation with Bluetooth-enabled devices such as PDA, Tablet-PC or Smart mobile phone.

TECHNICAL SPECIFICATIONS

Receiver Type	48 parallel channels, L1 C/A code
Accuracy	Position 2.5m CEP Velocity 0.1m/sec
Startup Time (average)	< 1sec hot start < 30sec cold start
Signal Reacquisition	1s
Sensitivity	-155dBm Re-acquisition -163dBm tracking -147dBm Cold Start
Update Rate	1Hz standard
Dynamics	4G (39.2m/sec ²)
Operational Limits	Altitude < 18,000m or velocity < 515m/s (COCOM limit, either may be exceeded but not both)
Protocol	NMEA-0183 V3.01 GPGGA, GPGLL, GPGSA, GPGSV, GPRMC, GPVTG, GPZDA 38400 baud, 8, N, 1
Datum	Default WGS-84 User definable
Bluetooth Interface of operation	SPP compatible, version 2.0 compliant, class-2 operation, 4dBm output level Up to 10m
LED Indicator	Blue - Bluetooth status Red - Battery low Green - Charging battery Yellow- GPS status
Switch	Tact switch ON / OFF
Battery	For battery socket Li-ION rechargeable battery (1000 mA)
Input Voltage	5V DC
Power Consumption	< 50mA (1Hz standard version)
Dimension	73mm L x 44mm W x 21mm H
Weight:	60g (Including Battery)
Operating Temperature	-40 °C ~ +85°C
Humidity	5% ~ 95%



Binary Messages

See *Binary Message Protocol User's Guide* for detailed descriptions.

CanMore Electronics Co., LTD.

4F.,No. 30, Sec.1,Jiafong 5th Rd., Jhubei City
Hsinchu County, 302, Taiwan

Phone +886 3 6586046

Fax +886 3 6583940

Email sales@canmore.com.tw

Website: [http:// www.canmore.com.tw](http://www.canmore.com.tw)

© 2000 CanMore Electronics Co., Ltd. All rights reserved.

Not to be reproduced in whole or part for any purpose without written permission of CanMore Electronics Co., Ltd. ("CMEC")
Information provided by CMEC is believed to be accurate and reliable. These materials are provided by CMEC as a service to its customers and may be used for informational purposes only. CMEC assumes no responsibility for errors or omissions in these materials, nor for its use. CMEC reserves the right to change specification at any time without notice.

These materials are provided "as is" without warranty of any kind, either expressed or implied, relating to sale and/or use of CMEC products including liability or warranties relating to fitness for a particular purpose, consequential or incidental damages, merchantability, or infringement of any patent, copyright or other intellectual property right. CMEC further does not warrant the accuracy or completeness of the information, text, graphics or other items contained within these materials. CMEC shall not be liable for any special, indirect, incidental, or consequential damages, including without limitation, lost revenues or lost profits, which may result from the use of these materials.

CMEC products are not intended for use in medical, life-support devices, or applications involving potential risk of death, personal injury, or severe property damage in case of failure of the product.